## **BALANCE**

Design by Jordi Vilardell.



Reference

5189.

Application

Floor Lamps

## Description

Floor light which also acts as a ceiling light. Designed by Jordi Vilardell. Thanks to a small pull chord located at the bottom of the aluminium-weft shade, which also serves as a switch, the shade can be moved to the right or left and up and down while remaining parallel to the floor at all times. It has a dimmer switch in the cable. Available in chrome and matt nickel.

Diffuser

Aluminium-weft diffuser

Materials

Tubo vertical: Aluminio

Base: Steel

Brazo: Acero inoxidable Pantalla: Trama de aluminio

Finish



5189-01 Chrome (Metallic finish)




5189-18 Matt graphite lacquer (RAL 7016)



5189-30 Matt nickel (Metallic finish)

Sketch



**Electrical characteristics** 

3 x E27 230V 70W Eco

Total 210.0 W





Fixture: 839 lm 4 lm/W

Driver included: CC - Constant Current 100-240V 50/60Hz

**Technical characteristics** 

- Dimmer on the cable

**Physical characteristics** 

 $3 \text{ Box} / 2.44 \text{ x } 0.18 \text{ x } 0.19 \text{ m.} / \text{Vol. } 0.3475 \text{ m}^3 /$ Gross weight 53.4 kg. / Net weight 48.1 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 43.70% Isolux: Floor Coordinate system : CG Light position : Total flux : 1920.00 lm X=0.00m Y=0.00m Z=3.00m

Maximum value: 88.28 cd/klm Light position: C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates









